

# s.QUAD Voice 360

SWISSPHONE



s.ONE  
ready

## The Smart Tone & Voice Pager with a Twist

Swissphone's new generation of pagers impresses users with state-of-the-art functional design and unique performance features. Its innovative design makes the s.QUAD Voice 360 extremely robust and very comfortable to wear. Its rotary knob controls volume and selects profiles, giving the user full control while the pager is still on the belt. Secure receipt of messages and loud alerting take center stage. With a sensitivity of  $\leq 2.0 \mu\text{V/m}$ , the s.QUAD is the best in its class. The s.QUAD Voice 360 can be updated by firmware to a digital paging receiver (POCSAG), or can work in both modes in parallel as a single device. This option perfectly supports a smooth migration to digital alerting.

### s.ONE software solution from Swissphone

Together with the modular s.ONE software solution from Swissphone and a smartphone interface via Bluetooth, the s.QUAD offers additional applications for complementary alerting.

- Hybrid alert: Radio alerting combined with IP alerting
- Monitoring: Information on the response of the team
- Resources: Overview of availability
- Reports: Evaluation of the operations at the push of a button

### Key performance features

- » Excellent reception
- » Programmable receiving frequency within switching bandwidth. Wide PLL up to 10 MHz (VHF)
- » 64 addresses (2-tone and 5/6-tone)
- » 64 selection and switching profiles possible
- » Alerting volume  $> 95 \text{ dB(A)}$  at 30 cm / 12 inches distance
- » Multi-colored alarm LED
- » High-resolution display (for message display via bluetooth)
- » Extremely robust and water-proof
- » Up to 16 minutes of stored voice memory
- » Optional: Multi-channel in one device
- » Optional: Digital alerting with POCSAG
- » Optional: Analog and digital as one single device



# s.QUAD Voice 360

	Performance features	Technical data
<b>Standards, compliance, environmental conditions</b>	Standards	ETSI EN 300 296 EN 60068-2-27 (shock) EN 60068-2-6 (vibration) EN 60068-2-32 EN 60529:1991 + A1 : 2000 IP67 ETSI EN 300 390
	Temperature range	-4 °F to +131 °F / -20 °C to +55 °C
<b>Main characteristics</b>	Frequency bands <small>(additional frequencies on request)</small>	VHF 2 m band      150-160/146-155/155-164/164-174 MHz
	Frequency processing	PLL, frequency can be adjusted in the entire frequency band with programming software
	Channel spacing	12.5, 20/25 kHz
	Sensitivity* <small>* Typical value at 2 m Band (best position on «salty man»)</small>	Better than 2.0 µV/m
	Signal strength display (RSSI)	5 column display. More columns means stronger signal
	Addresses	<ul style="list-style-type: none"> <li>• 64 addresses 2-tone or longtone</li> <li>• 64 address names with eight characters</li> <li>• ZVEI 1 / CCIR1 / free (5/6-tone option)</li> </ul>
	Alerting	<ul style="list-style-type: none"> <li>• Volume &gt; 95 dB(A) at 30 cm / 12 inches distance</li> <li>• Vibration alarm</li> <li>• Multi-colored alarm LED, programmable</li> <li>• Up to 64 user profiles or user switchable</li> </ul>
	Voice Memory	Up to 16 minutes stored voice
Options	Multi-channel (8), 5/6 tone decoding	
<b>Display and housing</b>	Display	<ul style="list-style-type: none"> <li>• Greyscale display with high resolution (146 x 128 pixels, 106 DPI)</li> <li>• White backlight</li> <li>• Displays up to 250 characters per page</li> </ul>
	Dimensions (H x W x D)	3.19 x 2.52 x 0.87 inches / 81 x 64 x 22 mm
	Weight (including battery)	3.81 oz / 108 g
<b>Power management</b>	Type of battery	NiMH plus battery or alkaline battery (standard AA battery)
	Operating times (eco mode)	<ul style="list-style-type: none"> <li>• Alkaline battery (1.5 V): 160 hours</li> <li>• NiMH plus battery (1.2 V/2000mAh): 160 hours</li> </ul>
<b>Accessories</b>	Programming software	Programming kit with Windows-based programming software
	Chargers	Versatile charging devices
	Carrier bags	<ul style="list-style-type: none"> <li>• Clip holster</li> <li>• Leather case</li> <li>• Safety chain</li> </ul>

Specifications are subject to change without notice.



## POCSAG Option (Two in One):

s.QUAD Voice works in parallel on the existing analog 2-tone and the future-proof digital POCSAG network. With this software option the s.QUAD pager can receive voice calls and text messages from two different networks. This two-in-one option perfectly supports the migration from analog to digital.



## s.ONE ready

s.QUAD was designed to enable the combination of various s.ONE software solutions for clear alerting. Fire Chiefs or Dispatchers can, for example, use their smartphones or computer screens to display how many emergency personnel are available and how many will actually respond.



## Bluetooth

Bluetooth technology makes it possible to connect the s.QUAD with a compatible smartphone and ultimately with various s.ONE software solutions from Swissphone. This includes, among other things, the display of the availability of the emergency services and the resources as well as the strength of the team.



Swissphone, LLC  
1194 West Ash Street, Suite C  
Windsor, CO 80550  
Tel. +1 800 596 1914  
Fax +1 970 460 3014  
E-Mail info.usa@swissphone.com